

Scapa 149R

Low-Residue Duct Tape

DESCRIPTION

Scapa 149 is a laminated cloth, single coated with a low-residue, natural rubber adhesive.

APPLICATIONS

- Applications requiring a conformable product and low-residue performance.
- Taping of metal ductwork.

PRODUCT BENEFITS

- Easily torn by hand and will not twist or curl during application.
- Leaves no residue upon removal.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	8.5 (0.22)	Mils (mm)	REN TM 20
Adhesion to Steel	30 (8.3)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	22 (6.1)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	24 (107)	lbs. / inch (N/25mm)	ASTM D 1000

STANDARD PRESENTATIONS

RECOMMENDATIONS

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65° F (18°C) or above.

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.