



Scapa 174

Double Sided Cloth Tape - Natural, Rubber Resin

DESCRIPTION

Scapa 174 is a double-sided cloth tape with a woven cotton cloth carrier and an aggressive, natural rubber adhesive. This product is supplied on an easy-release white paper or poly liner.

APPLICATIONS

- Carpet installation where a more aggressive adhesive is required.
- Print plate mounting.
- Temporary mounting for assembly or machining operations.

PRODUCT BENEFITS

- Easy unwind and hand tearable
- Clean peel after use and leaves no residue upon removal.
- Good adhesion to a range of surfaces.
- Adhesive provides good shear resistance.
- Service temperature: -15°C to +70°C / +160°F.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Tape Thickness (Without Liner)	12.5 (0.318)	Mils (mm)	REN TM 20
Adhesion to Steel - Liner Side	50 (13.9)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Steel - Exposed Side	50 (13.9)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	28 (125)	lbs. / inch (N/25mm)	
Elongation at Break	12	%	ASTM D1000

Version: 33 Generated Date: 10 May 2024 Page: 1 of 2

www.scapaindustrial.com Product Code: 174

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

• Colours: White

• Core: 76mm Scapa branded or neutral cardboard

Packaging: Bulk

Roll Length: 25 metres

• Roll Width: 24, 48, 72, 310, 1,448 mm

Note:

Other lengths and widths (50 mm in Europe) are available on request.

RECOMMENDATIONS

The roll should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperature climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease or other contaminants.

 Version: 33
 Generated Date: 10 May 2024
 Page: 2 of 2

www.scapaindustrial.com Product Code: 174