

Scapa 3175

Extra Strong, Waterproof Cloth Tape

DESCRIPTION

Scapa 3175 is an extra strong waterproof cloth tape, coated with an aggressive pressure sensitive solvent free rubber resin adhesive. Ideal for a wide range of applications within construction, agriculture, arts and entertainment and industry. Available in a range of colours.

APPLICATIONS

- Can be used as a premium cloth tape for multi purpose sealing, bundling, holding and protection applications
- Tough and durable for maintenance and repair applications
- Identification, colour coding and marking within arts and entertainment applications
- Sealing and holding applications within agriculture
- Carpet joining and edging
- HVAC and general building applications

PRODUCT BENEFITS

- Easy to use, unwind and tear by hand
- Good initial tack and high adhesion to a range of surfaces
- Weather proof and moisture proof
- Good corrosion and abrasion resistance
- Available in a range of colours
- Solvent free adhesive, low VOC content and RoHS compliant
- Strong and robust yet conformable
- Good temperature range performance

TECHNICAL PROPERTIES

| Technical Property | Nominal Value | Unit | Test Method |
|---------------------------|---------------|----------|-------------|
| Thickness | 0.23 | mm | AFERA 5006 |
| Tensile Strength | 45 | N/cm | AFERA 4001 |
| Adhesion to Steel | 4.1 | N/cm | AFERA 4001 |
| Adhesion to Backing | 3 | N/cm | AFERA 4001 |
| Service Temperature Range | -15 to 80 | °C to °C | - |

STANDARD PRESENTATIONS

- Roll Length: 50m
- Roll Width: 50mm
- Core Diameter: 76mm cardboard
- Packaging: Bulk packed with interleaving between layers or shrink wrapped in packs of 4*

Note:

Other sizes and colours may be available on request

** dependant on item ordered*

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climatic environment, but should not be less than two years from date of manufacture, if stored in a moderate climate and good conditions.