



# **Scapa 9064**

## Kraft Paper Packaging Adhesive Tape

## **DESCRIPTION**

Scapa 9064 is a kraft paper coated with a rubber resin adhesive system, with  $100\mu$  total thickness and recommended for general bundling and packaging applications.

#### **APPLICATIONS**

- · Bag sealing.
- Box sealing.
- Bundling.
- Suitable for a variety of medium to light domestic packaging and sealing applications at home or in the
  office.

#### **PRODUCT BENEFITS**

- Easy unwind.
- · Very high tack.
- Solvent free.
- Printable with aqueous tints.
- Applicable by hand or with Scapa HD209 or HD210 dispensers.
- Continuous temperature resistance: +50°C.

## **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	5.5	N/cm	AFERA 4001
Elongation at Break	7	%	AFERA 4005
Tensile Strength	45.0	N/cm	AFERA 4004
Total Thickness	0.100	N/cm	AFERA 4006

Version: 6 Generated Date: 16 May 2024 Page: 1 of 2

www.scapaindustrial.com Product Code: 9064

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

### STANDARD PRESENTATIONS

• Colours: Kraft

Core: 76mm Scapa branded cardboard core

Packaging: ConcertinaRoll Length: 50 metres

• Roll Width: 38, 50 and 75mm

#### RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Version: 6 Generated Date: 16 May 2024 Page: 2 of 2

www.scapaindustrial.com Product Code: 9064