



Scapa BB100

Vapour Barrier High Performance Adhesive

DESCRIPTION

Scapa BB100 is a thixotropic adhesive without solvents for adhering films. It uses a strong adhesive substance made from acrylic and is designed to be applied to different substrates to join vapour barriers in new constructions and in renovations.

APPLICATIONS

- For joining vapour barriers on all construction materials (wood, fibreboard, OSB panels, chipboard, plaster board, concrete, bricks, PE or PVC components).
- Suitable for polymer films, aluminium, Kraft paper, non woven.

PRODUCT BENEFITS

- Odourless
- Contains no harmful substances
- Reliably absorbs all structural movements
- Solvent free :Resistant to aging
- Quick and reliable application
- Extremely water-proof on different substrates
- Strong adhesion to different materials

TECHNICAL PROPERTIES

STANDARD PRESENTATIONS

Version: 5 Generated Date: 15 May 2024 Page: 1 of 2

www.scapaindustrial.com Product Code: BB100

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Note:

Packaging: 310ml cartridge 20 cartridges per box

RECOMMENDATIONS

The cartridges should be stored sealed closed in their original packaging in a dry and cool place. A maximum use by date of strictly 24 months from the date of manufacture is recommended.

Surfaces to which the adhesive is to be applied must be clean, dry and free of all traces of dust, grease, oil or any other contaminating agent.

Version: 5 Generated Date: 15 May 2024 Page: 2 of 2

www.scapaindustrial.com Product Code: BB100