

Scapa D200

Double Sided Polyester Tape - Differential Rubbers, Clean Removal, 0.07mm

DESCRIPTION

Scapa D200 is a thin double sided tape based on a 23 micron polyester film coated on both sides with a rubber based adhesive system with a 98 g/m² white paper release liner, with 0.07 mm total thickness. It is recommended for a variety of bonding, mounting and laminating applications where high plasticiser resistance is required.

APPLICATIONS

- Temporary bonding of highly plasticised PVC mats on wooden varnished flooring or existing sports floor covering.

PRODUCT BENEFITS

- Service temperature: -10°C to +70°C.
- Thin bonding solution.
- High shear resistance.
- Extreme plasticiser resistance.
- Clean removal (does not leave adhesive residue).

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel - Open Side	4.6	N/cm	AFERA 4001
Adhesion to Steel - Liner Side	6.5	N/cm	AFERA 4001
Adhesive Thickness - Liner Side	0.035	mm	AFERA 4006
Adhesive Thickness - Open Side	0.015	mm	AFERA 4006
Carrier Thickness	0.023	mm	AFERA 4006
Liner Thickness	0.089	mm	AFERA 4006
Total Thickness (Without Liner)	0.07	mm	AFERA 4006

Version: 7

Generated Date: 11 May 2024

Page: 1 of 2

www.scapaindustrial.com

Product Code: D200

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

- Colours: Transparent
- Core: 76mm Scapa branded cardboard
- Packaging: Bulk
- Roll Length: 50 metres
- Roll Width: 96 and 1,360mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at 6 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.