

## Scapa 1252

### BOPP Packaging Adhesive Tape

---

#### DESCRIPTION

Scapa 1252 is a 28 micron bi-axially oriented polypropylene film coated with a rubber based adhesive system, with 45 $\mu$  total thickness and recommended for general bundling and packaging applications.

#### APPLICATIONS

- Bag sealing.
- Box sealing.
- Bundling.
- Suitable for a variety of medium to light domestic packaging and sealing applications at home or in the office.

#### PRODUCT BENEFITS

- Easy unwind.
- Very high tack.
- Moisture and chemical resistant.
- Solvent free.
- Applicable by hand or with Scapa HD209 or HD210 dispensers.
- Continuous temperature resistance: +50°C.

*Accreditation:*

*Conforms to the technical requirements of BS 3887*

## TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	4.5	N/cm	AFERA 5001
Elongation at Break	170	%	AFERA 5004
Tensile Strength	39	N/cm	AFERA 5004
Total Thickness	0.045	mm	AFERA 5006

## STANDARD PRESENTATIONS

- Colours: Buff, Transparent and White
- Core: 76 mm Scapa branded cardboard core
- Packaging: Flat shrink pack
- Roll Length: 66, 100 and 132 metres
- Roll Width: 50 mm

*Note:*

*Other widths may be available upon previous request and will be always subject to minimum order quantities*

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.

Under these conditions, the storage life of the tape in a temperate climate will be at least one year. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.