



## Scapa 125R

### Vinyl Coated Cloth Tape - 10.5 mils

#### DESCRIPTION

Scapa 125 is a waterproof, vinyl coated cloth, single coated with a natural rubber adhesive.

#### APPLICATIONS

- Temporary repairs.
- Floor marking.
- Waterproof packaging.
- Securing cables, props and lighting equipment.

#### PRODUCT BENEFITS

- Leaves no adhesive residue after temporary use
- Easy unwind.
- High tensile strength.
- High tack and ultimate adhesion.

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	10.5 (0.27)	Mils (mm)	PSTC - 133
Adhesion to Steel	26 (7.2)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	12 (3.3)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	35 (155.7)	lbs. / inch (N/25mm)	ASTM D 1000
Operating Temperature	32 - 122 (0 - 50)	°F (°C)	-

## STANDARD PRESENTATIONS

- Colours: White, Black or Grey

## RECOMMENDATIONS

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE: 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.

2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.