



## Scapa 145R

### Heavy-Duty Cloth Tape

#### DESCRIPTION

Scapa 145 is a laminated polyethylene cloth, single coated with an aggressive natural rubber adhesive.

#### APPLICATIONS

- Taping of metal ductwork.
- Heavy-duty applications requiring high strength and / or high level superior adhesion.

#### PRODUCT BENEFITS

- Excellent adhesion to a wide variety of materials and surfaces.
- Backing is release-coated to provide easier unwind.

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	17 (.432)	Mils (mm)	REN TM 20
Adhesion to Steel	70 (19)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	45 (12)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	40 (175)	lbs. / inch (N/25mm)	ASTM D 1000

#### STANDARD PRESENTATIONS

## RECOMMENDATIONS

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

### NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.