

## Scapa 1500

### Glass Grid Adhesive Tape

---

#### DESCRIPTION

Scapa 1500 is a glass grid tape coated with a rubber adhesive. Scapa 1500 is available in white.

#### APPLICATIONS

- Repairing cracks or holes in walls
- Joining of dry wall panels

*Note:*

**NOTE: DO NOT USE ON THE CEILING**

#### PRODUCT BENEFITS

- Allows a neat job, no bubbles or cracking on the join
- Strong transverse and longitudinal mechanical resistance
- Allows coating to be applied in a single stroke
- Easy and quick application
- Good adhesion to plaster

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Elongation at Break	5	%	AFERA 4005
Tensile Strength	90	N/cm	AFERA 4004
Total Thickness	0.20	mm	AFERA 4006

## STANDARD PRESENTATIONS

- Core: 76mm
- Packaging: Individually film wrapped
- Roll Length: 45m, 153m
- Roll Width: 48mm

*Note:*

*Note: Information on stock items, non-standard sizes, and lead times is available on request*

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging at a temperature between +10°C and +30°C until required for use.

The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Service life will vary with conditions of use and is affected by climatic environment, but it is recommended that the product should be used within 24 months of date of manufacture, if stored in good conditions.