

## Scapa 1695

### Metalised Polyester Adhesive Tape

#### DESCRIPTION

Scapa 1695 is a 25µm coloured metalised polyester film coated with an acrylic adhesive system, with 70µm total thickness and recommended for general splicing, decorative and sealing applications.

#### APPLICATIONS

- Decorative edging and reinforcing tape.
- Double glazed sealing.
- Repairing and splicing thermal blankets and screens in the horticultural industry.
- Splicing and web defects reflective tape for sensors.
- Suitable for a variety of long ageing and/or temperature resistant decorative, sealing and splicing applications.

#### PRODUCT BENEFITS

- Good shear resistance.
- High tensile strength.
- Long ageing adhesive.
- Wide continuous temperature resistance.
- Service temperature:: -30°C to +100°C.

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	4.5	N/cm	AFERA 5001
Elongation at Break	100	%	AFERA 4005
Tensile Strength	30	N/cm	AFERA 4004
Total Thickness	0.07	mm	AFERA 5006

## STANDARD PRESENTATIONS

- Colours: Silver
- Core: 76 mm Plastic core
- Roll Length: 66 meters
- Roll Width: 25, 38 and 50 mm

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.