

Scapa 2244

uPVC Surface Protection Red Film

DESCRIPTION

Scapa 2244 is a 37 μm UPVC film coated with a low tack rubber/resin solvent based adhesive system, with 52 μm total thickness and recommended for temporary masking and protective applications.

APPLICATIONS

- Temporary protection of metal, plastic and wood panels during fabrication, storage and transportation, except for polycarbonate and copper.
- Suitable for a variety of indoor and limited outdoor protective applications.

PRODUCT BENEFITS

- Easy unwind.
- Low tack.
- Continuous temperature resistance: +60°C.
- Residues free after removal.
- Printable.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	0.7	N/25mm	AFERA 5001
Tensile Strength	48	N/cm	AFERA 4004
Elongation at Break	45	%	AFERA 4005
Total Thickness	0.052	mm	AFERA 5006

STANDARD PRESENTATIONS

- Colours: Teinté rouge
- Core: 76 mm carton - marque Scapa
- Packaging: Sacs plastiques
- Roll Length: 100 mètres
- Roll Width: 25, 38 et 50 mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.