



Technical DATA

Scapa 225R

Vinyl Coated Cloth Tape

DESCRIPTION

Scapa 225 is a waterproof vinyl coated cloth, single coated with a natural rubber pressure sensitive adhesive

APPLICATIONS

- Securing cables, props and lighting equipment.
- Bundling.
- Waterproof wrapping.
- Packaging.
- Color coding.
- Floor marking.
- Temporary repairs.

PRODUCT BENEFITS

- High tack.
- High tensile strength.
- Easy unwind.
- Printable.
- High performance cloth tape with high strength and adhesion.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	12 (0.31)	Mils (mm)	REN TM 20
Adhesion to Steel	60 (16)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	28 (8)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	44 (193)	lbs. / inch (N/25mm)	ASTM D1000

STANDARD PRESENTATIONS

RECOMMENDATIONS

Application to Surface:

Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65 F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.