

## Scapa 2290

### uPVC Packaging Adhesive Tape

---

#### DESCRIPTION

Scapa 2290 is a 33 $\mu$  micron UPVC film coated with a rubber/resin solvent based adhesive system, with 51 $\mu$  total thickness and recommended for general bundling and packaging applications.

#### APPLICATIONS

- Suitable for a variety of medium to light domestic packaging and sealing applications at home or in the office.
- Bundling.
- Box sealing.
- Bag sealing.

#### PRODUCT BENEFITS

- Continuous temperature resistance: +60°C.
- Applicable by hand or with Scapa HD209 or HD210 dispensers.
- Printable.
- Moisture and chemical resistant.
- Low noise.
- High tack.
- Easy unwind.

#### *Accreditation:*

*Conforms to the technical requirements of BS3887*

## TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2	N/cm	AFERA 4001
Elongation at Break	60	%	AFERA 4005
Tensile Strength	48	N/cm	AFERA 4004
Total Thickness	0.051	mm	AFERA 4006

## STANDARD PRESENTATIONS

- Colours: Buff, Transparent and White
- Core: 76 mm Scapa branded cardboard core
- Packaging: Flat shrink pack
- Roll Length: 66, 100 and 132 metres
- Roll Width: 50 mm

*Note:*

*Other widths may be available upon previous request and will be always subject to minimum order quantities.*

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.