

Scapa 2500

Polyethylene Adhesive Tape

DESCRIPTION

Scapa 2500 is a polyethylene film coated with an acrylic adhesive system. Scapa 2500 is green.

APPLICATIONS

- Temporary masking of rough substrates such as stone, concrete, brick, etc.
- Masking during painting or projection of cement or plaster on facades.
- Masking during repairing or cleaning facades.

PRODUCT BENEFITS

- Very good adhesion on rough and difficult surfaces (wood, stone, facing, etc.)

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2	N/cm	AFERA 4001
Elongation at Break	200	%	AFERA 4005
Service Temperature	60	°C	Scapa
Tensile Strength	15	N/cm	AFERA 4004
Total Thickness	0.82	mm	AFERA 4006

STANDARD PRESENTATIONS

- Core: 76 mm Scapa
- Packaging: In bulk or individual plastic bag
- Roll Length: 33 metres
- Roll Width: 125, 200, 300, 400, 500 mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.