

Scapa 2745

PVC Adhesive Tape

DESCRIPTION

Scapa 2745 is a 0.13mm self-extinguishing soft PVC tape which combines the high flexibility of a superior soft PVC backing with the high grab and adhesion of an aggressive pressure sensitive rubber-based adhesive system. It has been designed for a variety of wrapping applications.

APPLICATIONS

- Harnessing.
- Protection of drink pythons.
- Suitable for a variety of wrapping applications where automatic taping is required.

PRODUCT BENEFITS

- Easy and smooth unwind.
- Good conformability.
- Conforms to the European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free).
- Continuous temperature +80°C.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	0.13	mm	CEI EN 60454
Tensile Strength	25	N/cm	CEI EN 60454
Elongation at Break	180	%	CEI EN 60454
Adhesion to Steel	1.5	N/cm	CEI EN 60454
Adhesion to Backing	1.5	N/cm	CEI EN 60454
Flammability	Self-extinguishing	-	CEI EN 60454

STANDARD PRESENTATIONS

- Colours: Black
- Core: 76 mm Scapa branded cardboard core
- Packaging: Bulk
- Roll Length: 125 metres
- Roll Width: 50; 75 and 100mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Use within 24 months of receipt. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. The tape should be applied with sufficient tension to ensure an optimum bonding and a minimum of two layers with a half overlap. The final layer should be wrapped with a lower tension to prevent flagging effects.