



## Scapa 2900

### Non-Adhesive Hazard Warning Polyethylene Tape

#### DESCRIPTION

Scapa 2900 is a 25 micron, low density polyethylene film red and white striped and recommended for hazard warning and safety applications.

#### APPLICATIONS

- Application temperature: 0°C to +50°C.
- Easy to use by hand.
- Outstanding conformability.
- Identification of potential danger areas (construction sites, marking off work areas, etc.)
- Hazard warning and safety non adhesive tape.

#### PRODUCT BENEFITS

- Service temperature: -0°C to +50°C.
- Easy to tie by hand.
- Excellent conformability.
- Suitable for indoor and protected outdoor environments.

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Temperature Fusion	100 - 120	°C	-
Total Thickness	0.25	mm	AFERA 4006

## STANDARD PRESENTATIONS

- Colours: Red and White striped
- Core: 76 mm cardboard core
- Packaging: Bulk
- Roll Length: 100 metres
- Roll Width: 50 mm

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from

dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.

Under

these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.