

Scapa 297

PVC Adhesive Tape for Protection and Repair

DESCRIPTION

Scapa 297 is PVC plasticized, coated with rubber adhesive. It exists in orange.

APPLICATIONS

- Premium PVC masking for exterior use (7 days)
- For smooth and slightly rough surfaces.
- All repair operations, marking, sealing, protecting, maintaining, tightness

PRODUCT BENEFITS

- Interior and exterior use
- Water and humidity resistant and barrier
- Very conformable
- Masking with all types of paints
- High tack

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	0.8	N/cm	AFERA 4001
Breaking Elongation	170	%	AFERA 4005
Operating Temperature	0° to +70°	°C	-
Tensile Strength	19	N/cm	AFERA 4004
Total Thickness	0.1	mm	AFERA 4006

STANDARD PRESENTATIONS

- Branding: No brand
- Core: 76mm
- Packaging: individual shrink with barcode
- Roll Length: 33m
- Roll Width: 50mm and 75mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants