

## Scapa 2994

### Outdoor Low-Tack Protection Tape

#### DESCRIPTION

Scapa 2994 is a single coated Polyethylene film, coated with a rubber based adhesive.  
Scapa 2994 is black.

#### APPLICATIONS

- For metallic surface protection in building (anodised aluminium profiles and window frames)
- The tape should perform well on most metal surfaces e.g. mild steel, stainless steel and aluminium.
- Outdoor protection of a wide range of metal and other articles during transportation and storage (e.g. anodized aluminium profiles, window frames and metal ladders)

#### PRODUCT BENEFITS

- Service temperature of 60°C
- Good UV resistance (up to 6 months outside)
- The tape is suitable for use either indoors or outdoors
- Resistant to moisture, many chemicals, such as dilute acids and alkalis, and salt solutions.
- Easy, clean removal from the protected article after use
- Easy hand tearability
- Easy unwinding

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Elongation at Break	360	%	AFERA 4005
Peel Adhesion	1.2	N/cm	AFERA 4001
Tensile Strength	20	N/cm	AFERA 4004
Total Thickness	0.123	mm	AFERA 4006
Unwinding strength	0.8	N/cm	AFERA 4013

Version: 10

Generated Date: 16 July 2024

Page: 1 of 2

www.scapaindustrial.com

Product Code: 2994

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

## STANDARD PRESENTATIONS

- Branding: Scapa / Barnier
- Core: 76mm
- Packaging: -
- Roll Length: 33m
- Roll Width: 50mm

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.