



Technical
DATA

Scapa 3130

Matte Waterproof Cloth Tape

DESCRIPTION

Scapa 3130 is a high quality 80 mesh, polyethylene coated waterproof cloth tape, coated with a pressure sensitive natural rubber resin adhesive and a superior matte finish. Scapa 3130 is available in a range of standard colours including black, white, blue, red, green and yellow, plus the specific shades Chromakey blue and green for the entertainment industry.

APPLICATIONS

- Ideal for general purpose applications where added strength, performance and low light reflectance is required.
- Book and spine binding.
- Joining and splicing applications.
- Floor marking on stages, film sets, etc.
- Colour coding and identification.
- Masking and marking of stage equipment.
- Temporary fixing and holding of wires and cables to floors and walls.

PRODUCT BENEFITS

- Good all round performance.
- Can be written on.
- Peels off cleanly after use, even after 6 weeks.
- Very easy tear by hand.
- Easy unwind for ease of use.
- Good initial tack and ultimate adhesion.
- Highly flexible and conformable to support use in difficult and uneven surfaces.
- Can be removed cleanly from surfaces after being in situ temporarily.
- Good strength and durability.
- Excellent waterproof properties.
- Excellent matt finish prevents the reflection of light.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Backing	14 (1.56)	Oz/Inch (N/cm)	IEC 454-2
Adhesion to Steel	27 (3.00)	Oz/Inch (N/cm)	IEC 454-2
Service Temperature	0-60°C	°C	-
Tensile Strength	31 (137.93)	lbs. / inch (N/25mm)	IEC 454-2
Thickness	11.4 (0.29)	Mils (mm)	Internal *

STANDARD PRESENTATIONS

- Core: 76mm Cardboard
- Packaging: Bulk packed using interleaving sheets between layers
- Roll Length: 50m
- Roll Width: 25mm, 38mm, 50mm, 75mm, 100mm

Note:

Note: Information on stock items, non standard sizes and lead times is available on request

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

The shelf life will vary depending on conditions of storage but should not be less than two years from the date of manufacture, if stored in a moderate climate and good conditions.