



Technical
DATA

Scapa 3162

Waterproof Cloth Tape - 0.18mm

DESCRIPTION

Scapa 3162 is a premium quality, higher adhesion version, polyethylene laminated waterproof cloth tape. It is coated with a pressure sensitive, natural rubber resin adhesive. Scapa 3162 is available in black, white and silver as standard.

APPLICATIONS

- Designed as a general purpose waterproof cloth tape for applications requiring additional strength and adhesion.
- Used for sealing, bundling, short term masking and protecting.
- Excellent for jointing polyethylene sheeting in asbestos removal applications.
- Suitable for double glazing unit sealing.
- Medium temperature duct sealing.
- Carpet joining and edging.

PRODUCT BENEFITS

- Good water resistance.
- Excellent adhesion and ultimate bond strength.
- Flexible and conformable.
- Service temperature: -15°C to +75°C.
- Good all purpose product.
- Easy unwind.
- Easy tear by hand.
- Good initial tack
- Good low temperature performance for winter applications
- REACH and RoHS compliant

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Backing	3.5	N/cm	IEC 60454-2
Adhesion to Steel	6.0	N/cm	IEC 60454-2
Breaking Strength	35	N/cm	IEC 60454-2
Thickness	0.18	mm	AFERA 5006*

STANDARD PRESENTATIONS

- Core: Scapa cardboard core as standard
- Packaging: Bulk packed with interleaving between layers or shrink wrapped in packs of 4 *
- Roll Length: 50m
- Roll Width: 50 and 75mm as standard. Other sizes on request.
- Colours: Available in silver, black and white as standard

Note:

** 50/75mm width rolls*

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climatic environment, but under these conditions it is recommended the product should be used within two years from date of manufacture.