



Technical
DATA

Scapa 3361

Unbleached Cotton Cloth Tape - 0.28mm

DESCRIPTION

Scapa 3361 is a general purpose unbleached cotton cloth tape with a pressure sensitive natural rubber resin adhesive. Scapa 3361 is available in a natural colour shade.

APPLICATIONS

- Protective masking and coverings for road "cat's eyes", manhole, covers etc. during roadworks and re-surfacing.
- Suitable for sealing, packaging, bundling and binding applications.
- Protection of sharp edges.
- Protection of polished surfaces and machine parts against corrosion or damage.

PRODUCT BENEFITS

- Service Temperature of 60°C.
- Can be written on.
- Strong and durable.
- Easy to tear by hand.
- Good initial tack and ultimate adhesion.
- Easy unwind properties.
- Conformable quality cloth tape.
- Abrasion resistant.
- Corrosion resistant.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2.6	N/cm	IEC 60454-2
Tensile Strength	70	N/cm	IEC 60454-2
Thickness	0.28	mm	Internal *

STANDARD PRESENTATIONS

- Core: Cardboard
- Packaging: Scapa branded, bulk packed using interleaving sheets between layers.
- Roll Length: 25m, 50m
- Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm

Note:

Note: Information on stock items, non-standard sizes, and lead times is available on request.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Service life will vary with conditions of use and is affected by climatic environment, but it is recommended that the product should be used within 6 months of date of manufacture, if stored in a moderate climate and good conditions.