



Technical
DATA

Scapa 3362

Unbleached Cotton Cloth Tape - 0.29mm

DESCRIPTION

Scapa 3362 is a general purpose unbleached cotton cloth tape with pressure sensitive, solvent free, natural rubber resin adhesive. Scapa 3362 is available in a natural colour shade.

APPLICATIONS

- Protective masking and coverings for road "cat's eyes", manhole covers, etc. during roadworks and re-surfacing.
- Protection of polished surfaces and machined parts against corrosion.
- Also suitable for use for heavy duty general purpose sealing, packaging, bundling and binding applications.

PRODUCT BENEFITS

- Corrosion resistant.
- Abrasion resistant.
- Flexible and highly conformable.
- Easy tear by hand.
- High initial tack and adhesion.
- Can be written on.
- An economic cloth tape for general purpose applications.
- Service temperature of: -10°C to +60°C.
- Uses only natural not solvent rubber in the adhesive system
- Strong and robust

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Thickness	0.29	mm	AFERA 5006*
Adhesion to Steel	3	N/cm	IEC 60454-2
Tensile Strength	70	N/cm	IEC 60454-2
Adhesion to Backing	1.4	N/cm	AFERA 4001

STANDARD PRESENTATIONS

- Roll Length: 25m, 50m
- Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm
- Core: Cardboard
- Packaging: Scapa branded, bulk packed using interleaving sheets between layers.

Note:

Note: Information on stock items, non-standard sizes, and lead times is available on request.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Shelf life will vary with conditions of use and is affected by climatic environment, but it is recommended that the product should be used within 6 months of date of manufacture, if stored in a moderate climate and good conditions.