



Scapa 442R

Utility-Grade Duct Tape

DESCRIPTION

Scapa 442 is a polyethylene-coated cloth, single coated with a high tack natural rubber adhesive.

APPLICATIONS

- Colour coding.
- General-purpose bundling and sealing.
- Hanging of poly sheeting.
- Taping of metal ductwork.

PRODUCT BENEFITS

- Superior adhesion to poly films.
- Easily torn by hand and will not twist or curl during application.
- High adhesion over a wide temperature range with no “edge-ooze”.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	8.5 (0.215)	Mils (mm)	REN TM 20
Adhesion to Steel	55 (15.3)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	35 (9.7)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	24 (105)	lbs. / inch (N/25mm)	ASTM D 1000

STANDARD PRESENTATIONS

- Branding: MAde in Canada core as standard
- Width: 48,72 and 96 mm as standard
- Standard length: 55m
- Colours: Available in silver and black as standard

RECOMMENDATIONS

Application to Surface:

Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65° F (18°C) or above.

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end