

Scapa 4472

Transfer Adhesive - Soft Acrylic, with Polyester Grid Reinforcement - 0.2mm

DESCRIPTION

Scapa 4472 FIX is an acrylic adhesive transfer tape 200 microns thick. It is reinforced by a polyester grid and protected by an 80 g / m² siliconised paper liner.

APPLICATIONS

- Permanent fixing on metallic and wooden frames.
- Fixing of all vapour barrier and sub-roof membranes, including Tyvek®.

PRODUCT BENEFITS

- Service temperature: -40°C to +120°C.
- Strong and permanent adhesion, to substrates with low surface energy such as Tyvek®.
- Very high tack.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	24	N/25mm	AFERA 5001
Tack	<2	N/25mm	PSTC 6
Total Thickness (excluding liner)	200	Microns	AFERA 5006
Thickness of Liner	67	Microns	AFERA 5006

STANDARD PRESENTATIONS

- Core: 76mm
- Packaging: Bulk or shrink wrapped with one front label
- Roll Length: 25 metres
- Roll Width: 19; 25; 38 mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature should be between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants, before application. .