

Scapa 5164

PVC Double Sided Foam Tape - White, Hard, Waterseal

DESCRIPTION

Scapa 5164 is a general purpose, hard and resilient double-sided PVC foam bonding tape. The product is white. The foam is predominantly closed celled. An acrylic pressure sensitive adhesive is coated on both sides, and the product has a white paper release liner. The material can be supplied with a green film liner facilitating automated application

APPLICATIONS

- For preventing electrolytic corrosion.
- Forms a compression water seal.
- For glazing.
- For automotive mirror mounting.
- For general mounting / bonding.

PRODUCT BENEFITS

- Pre-determined dimensional sealant reduces waste / clean to use.
- No known hazards associated with this product.
- Suitable for indoor and outdoor environments.
- Resistance to abrasion, corrosion and moisture.
- Very good ultraviolet {UV} light resistance.
- Paper release liner, reducing dimensional change during application.
- Good resistance to dilute acids and alkalis.
- Coated on both sides with a high quality pressure sensitive acrylic adhesive.
- Minimum 20% compression required to effect a water seal.
- Shelf life of 1 year from date of dispatch.
- Application temperature: +10°C to +40°C.
- Service temperature: -40°C to +70°C.
- Maximum recommended weight loading of 7 g/cm².

Accreditation:

Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free).
Compatible for full contact with Dow Corning® silicone sealants.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
10 Minute 180° Peel Adhesion	10	N/25mm	Scapa F9
500 hour Static Shear (Stainless Steel)	0.15	Kg/cm ²	Scapa F7
Dynamic Tensile Adhesion	25	N/cm ²	Scapa F19
Elongation at Break	220	%	Scapa F17
Foam Density	270	Kg/m ³	Scapa F2
Shore Hardness {OO} Scale	55	-	Scapa F16
Tensile Strength	110	N/cm ²	Scapa F17

STANDARD PRESENTATIONS

- Core: 76mm plastic
- Formats: Logs, Rolls, Spools
- Thickness : 0.8, 1.5, 3.0 mm

Note:

Thickness 4.5mm available as make to order.

RECOMMENDATIONS

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Recommended cleaning agent is Propan-2-ol, {IPA}. Apply even pressure when the product is applied.

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the shelf life of the tape is 12 months from the date of dispatch.

Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.