

Scapa 5169

PVC Double Sided Foam Tape - Black, Hard, Waterseal

DESCRIPTION

Scapa 5169 is a general-purpose, hard double-sided foam bonding tape. The product is black. The foam is predominantly closed celled. An acrylic pressure sensitive adhesive is coated on both sides, and the product has a paper release liner. The material can be supplied with a green film liner facilitating automated application.

APPLICATIONS

- For general mounting / bonding.
- For automotive mirror mounting.
- For glazing.
- Forms a compression water seal.
- For preventing electrolytic corrosion.

PRODUCT BENEFITS

- Maximum recommended weight loading of 7 g/cm².
- Application temperature: +10°C to +40°C.
- Service temperature: -40°C to +70°C.
- Shelf life of 1 year from date of dispatch.
- Minimum 20% compression required to effect a water seal.
- Coated on both sides with a high quality pressure sensitive acrylic adhesive.
- Good resistance to dilute acids and alkalis.
- Paper release liner, reducing dimensional change during application.
- Very good ultraviolet {UV} light resistance.
- Resistance to abrasion, corrosion and moisture.
- Suitable for indoor and outdoor environments.
- No known hazards associated with this product.
- Pre-determined dimensional sealant reduces waste.
- Clean to use.

Accreditation:

Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free).
Compatible for full contact with Dow Corning® silicone sealants.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
10 Minute 180° Peel Adhesion	10	N/25mm	Scapa F9
500 hour Static Shear (Stainless Steel)	0.15	Kg/cm ²	Scapa F7
Dynamic Tensile Adhesion	32	N/cm ²	Scapa F19
Elongation at Break	220	%	Scapa F17
Foam Density	270	Kg/m ³	Scapa F2
Shore Hardness {OO} Scale	60	-	Scapa F16
Tensile Strength	110	N/cm ²	Scapa F17

STANDARD PRESENTATIONS

- Core: 76mm plastic
- Formats: Logs, Rolls, Spools
- Thickness : 0.8, 1.5, 2.0, 3.0 & 4.5 mm

RECOMMENDATIONS

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Recommended cleaning agent is Propan-2-ol, {IPA}. Apply even pressure when the product is applied.

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the shelf life of the tape is 12 months from the date of dispatch.

Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.