

Scapa 6098

Polyethylene Adhesive Tape - Green, 0.12mm

DESCRIPTION

Scapa 6098 is a single sided tape, a polyethylene film coated with a rubber based pressure sensitive adhesive. Scapa 6098 is available in green.

APPLICATIONS

- Masking before painting or rendering of facades of buildings
- Short time masking (48 hours max) on concrete, plaster, wood, roughcasts.
- General purpose building tape for repairing, sealing, waterproofing, masking, protection

PRODUCT BENEFITS

- Sticks on all surfaces even when they are dusty or damp
- Good initial peel adhesion on polyethylene sheet
- Easy unwind in spite of a very aggressive adhesive
- Can be torn by hand
- Remains conformable and supple at low temperature in winter
- Flexible and conformable

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	1.6	N/cm	AFERA 4001
Elongation at Break	110	%	AFERA 4005
Service Temperature	60	°C	INTERNAL
Tape Thickness	0.120	mm	AFERA 4006
Tensile Strength	18	N/cm	AFERA 4004
Unwinding	1.3	N/cm	AFERA 4013

STANDARD PRESENTATIONS

- Roll Length: 33 metres
- Roll Width: 50 mm
- Core: 76 mm Scapa/Barnier
- Packaging: Wrap

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be one year. Usage is recommended within one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.