

Scapa 6990

Building PVC tape

DESCRIPTION

Scapa 6990 is plasticised PVC, coated with an adhesive rubber compound. Scapa 6990 is orange.

APPLICATIONS

- Masking before painting or rendering of facades of buildings
- Any marking, repair, covering, protection, maintenance, and sealing job

PRODUCT BENEFITS

- Made in France
- Conformable and flexible
- Water vapour or moisture barrier
- Hand-tearable
- Good adhesion on all surfaces
- Good immediate adhesion
- Outside and inside use

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion on Steel	0,7	N/cm	AFERA 5001
Elongation at Break	210	%	AFERA 5004
Total Thickness	0,10	mm	AFERA 5006
Tensile Strength	28	N/cm	AFERA 5004
Tack (Rolling Ball Method)	2	cm	PSTC 6
Temperature Resistance	70	°C	-

STANDARD PRESENTATIONS

- Core: 76mm
- Packaging: Individual packaging with barcode label
- Roll Length: 30M
- Roll Width: 48mm

RECOMMENDATIONS

The rolls should be stored flat in the original packaging, protected from dust, light, humidity and evaporating solvents, at a temperature between +10°C and +30°C. Under these conditions the shelf life of the rolls in a temperate climate should not be allowed to exceed 12 months.

Surfaces should be clean, dry and free from dust, grease, oil and any other contaminant