

Scapa 6991

Plasticised, Self-Adhesive PVC

DESCRIPTION

Scapa 6991 is a plasticised PVC, coated with an adhesive rubber compound. Scapa 6991 is orange or white

APPLICATIONS

- Any marking, repair, covering, protection, maintenance, and sealing job
- Masking before painting or rendering of facades of buildings

PRODUCT BENEFITS

- Water vapour or moisture barrier
- Hand-tearable
- Very easy to handle
- Outdoor / Indoor
- Very Conformable
- Aggressive Adhesive
- Can be used on all painted surfaces

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Overall Thickness	0.10	mm	AFERA 4006
Tearing Strength	19	N/cm	AFERA 4004
Elongation at Break	170	%	AFERA 4005
Adhesive Strength on Steel Open side	0.8	N/cm	AFERA 4001
Temperature Stability	70	°C	-

STANDARD PRESENTATIONS

- Roll Length: 33 metres

RECOMMENDATIONS

The rolls should be stored flat in the original packaging, protected from dust, light, humidity and evaporating solvents, at a temperature between +10°C and +30°C. Under these conditions the shelf life of the rolls in a temperate climate should not be allowed to exceed 12 months.

Surfaces should be clean, dry and free from dust, grease, oil and any other contaminant