



Scapa 7022

Polypropylene Adhesive Tape Reinforced with Woven Glass Fibre

DESCRIPTION

Scapa 7022 is an ultra resistant polypropylene adhesive tape reinforced with woven glass fibre reinforcement, very hard-wearing. Scapa 7022 is coated with a rubber adhesive that is pressure sensitive, with a total thickness of 110µm, and recommended for all sealing, packaging and palletisation applications.

APPLICATIONS

- Strengthened sealing of cartons
- Hard-wearing packaging
- Palletisation of boxes
- Suitable for all medium and heavy sized packaging at home, the office and in all industrial environments
- Strapping for heavy items, making pallets safe and strengthening parcels

PRODUCT BENEFITS

- A great resistance to breaking lengthwise and crosswise
- Resistant to impacts during transportation

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	6.6	N/cm	AFERA 5001
Elongation at Break	5	%	AFERA 5004
Tensile Strength	160	N/cm	AFERA 5004
Total Thickness	110	μm	AFERA 5006

 Version: 8
 Generated Date: 17 May 2024
 Page: 1 of 2

www.scapaindustrial.com Product Code: 7022

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

• Packaging: Individual, shrink wrap with 2 labels

Roll Length: 50 metresRoll Width: 50mm

RECOMMENDATIONS

The rolls must be stored flat in their original packaging, protected from dust, light, damp and solvent fumes at a temperature between 15°C and 25°C inclusive. In these conditions the storage time in a temperate climate must not exceed 12 months.

Surfaces must be clean, dry and free from dust, grease, oil or any other contaminant.

Version: 8 Generated Date: 17 May 2024 Page: 2 of 2

www.scapaindustrial.com Product Code: 7022