



## M001-C22A

### Clear Carpet Protection Film

#### DESCRIPTION

Clear Carpet Protection Film is a clear low density polyethylene (LDPE) film, single coated with a water based acrylic adhesive

#### APPLICATIONS

- Temporary protective film for most synthetic carpets

#### PRODUCT BENEFITS

- Blend of LLDPE/PE film is resistant to tears or punctures from tools or shoe heels
- For use up to 45 days
- Protects from dirt, paint spills, dust, construction debris, and damage
- Can be applied by hand or with an applicator

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Peel Adhesion	25.8 (7.2)	Oz/Inch (N/25mm)	PSTC 101 Mod./180 <sup>o</sup> Initial to SS
Carrier Thickness	2.0	Mils	-
Carrier Colour	Clear	-	-

#### STANDARD PRESENTATIONS

- Roll Width: 48 inches (122 cm)
- Roll Length: 200 ft (61 m)

## RECOMMENDATIONS

Application to Primary Surface: Apply the adhesive side to the surface. Apply firm pressure. Recommended application temperature to achieve best results is 65° F (18° C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65° F (18° C) or above.

### NOTE:

- 1) When applying pressure sensitive adhesive films to any surface, be sure that the surface is dry, free from oil or other surface contaminants such as dirt, dust, or release agents.
- 2) Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C).
- 3) Not recommended for in high humidity conditions or in outdoor applications.