



M001-C50B

Clear Carpet Masking

DESCRIPTION

Clear Carpet Masking is a linear low density polyethylene (LLDPE) film, single coated with a water based acrylic adhesive. The film is wound, adhesive side out, on a 0.25 inch fiber core.

APPLICATIONS

- Temporary protective film for most synthetic carpets

PRODUCT BENEFITS

- Blend of LLDPE/PE film is resistant to tears or punctures from tools or shoe heels
- For use up to 45 days
- Reverse wound for easy roll out
- Protects from dirt, paint spills, dust, construction debris, and damage
- Can be applied by hand or with an applicator

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Peel Adhesion (PSTC 101 Mod./180°) Initial to SS (20 min. @ RT)	22 (6.0)	Oz/Inch (N/25mm)	PSTC 101 Mod./180° Initial to SS
Carrier Thickness	2.1	Mils	-
Tensile Strength - MD	9149	PSI	-
Elongation at Break MD	801	%	-

STANDARD PRESENTATIONS

- Roll Width: 24, 36, or 48 inches
- Roll Length: 200, 300, or 500 feet

Note:

48 inch rolls are available in 200 or 300 foot length only

RECOMMENDATIONS

Application to Primary Surface: Apply the adhesive side to the floor surface. Apply firm pressure. Recommended application temperature to achieve best results is 65° F (18° C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65° F (18° C) or above.

NOTE:

- 1) When applying pressure sensitive adhesive films to any surface, be sure that the surface is dry, free from oil or other surface contaminants such as dirt, dust, or release agents.
- 2) Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Not recommended for in high humidity conditions or in outdoor applications.