



Trim Tack M001-W50B

White Carpet Masking

DESCRIPTION

Carpet Protection Film is a durable polyethylene film, single coated with a water based acrylic adhesive, and wound on a three inch core.

APPLICATIONS

- Temporary protection for most synthetic carpets

PRODUCT BENEFITS

- LDPE film is resistant to tears or punctures from tools or shoe heels
- For use up to 45 days
- Reverse wound for easy roll out
- Protects from dirt, paint spills, dust, construction debris, and damage
- Can be applied by hand or with an applicator
- Available in widths up to 48 inches

TECHNICAL PROPERTIES

| Technical Property | Nominal Value | Unit | Test Method |
|---------------------------------|---------------|---------------------|------------------------------------|
| Peel Adhesion | 22 (6.0) | Oz/Inch (N/25mm) | PSTC101 mod. Initial to S. @ RT |
| Tensile Strength - Longitudinal | 10962 | PSI | - |
| Elongation | 916 | % | - |
| Thickness of Carrier | 3.0 | Mils | - |

STANDARD PRESENTATIONS

- Colours: White or Clear
- Roll Width: 24 or 36 inches
- Roll Length: 200, 300, or 500 feet
- Core Internal Diameter: 3 inches

RECOMMENDATIONS

Application to Primary Surface: Apply the adhesive side to the floor surface. Apply firm pressure.

Recommended application temperature to achieve best results is 65° F (18° C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65° F (18° C) or above.

NOTE:

When applying pressure sensitive adhesive films to any surface, be sure that the surface is dry, free from oil or other surface contaminants such as dirt, dust, or release agents.

Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Not recommended for in high humidity conditions or in outdoor applications.