



## Scapa M003-F

### Scapa Foam Sticky Rollers

#### DESCRIPTION

Foam Sticky Rollers are made from a poly film/foam laminate coated with a water based acrylic adhesive. Each replaceable cartridge consists of a roll of adhesive coated substrate perforated into removable sheets. Microban® infused technology protects the product from microbes, mold, and fungus.

#### APPLICATIONS

- Remove contaminating particles from floors, walls, ceilings, tabletops and many other surfaces

#### PRODUCT BENEFITS

- As simple to use as a common paint roller
- Conforms to slightly irregular surfaces
- Microban® infused technology inhibits the growth of microbes, mold, and fungus trapped on the film surface.
- When the roll becomes too soiled to pick up any more contaminants, simply peel off the top layer at perforations to expose a clean layer
- Wound on a plastic non-contaminating core for added strength and durability
- Roller handles are sold separately
- Telescopic extension poles are available

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Peel Adhesion	12.5 (3.5)	Oz/Inch (N/25mm)	PSTC 101 Mod./180° Initial to SS
Liner Thickness	1/32 (0.79)	Inch (mm)	-
Carrier Thickness	2.4	Mils	-

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

## STANDARD PRESENTATIONS

- Branding: Markel TRIM TACK®
- Roll Width: Available in 9, 12, or 18 inch

*Note:*

*9 inch - 20 sheets, 11.5 inch perforation length, 1.5 inch diameter core, packaged 4 per case*

*12 inch - 20 sheets, 16 inch perforation length, 3 inch diameter core, packaged 4 per case*

*18 inch - 20 sheets, 16 inch perforation length, 3 inch diameter core, packaged 4 per case*

## RECOMMENDATIONS

Application to Primary Surface: Mount cartridge to roller handle. Roll cartridge over soiled surface to remove debris.

Recommended application temperature to achieve best results is 65°F (18°C) or above.

NOTE:

- 1) When applying pressure sensitive adhesive films to any surface, be sure that the surface is dry, free from oil or other surface contaminants.
- 2) Shelf life is 18 months from date of shipment when stored in a cool dry place below 76°F (24°C)