

Scapa Mask 1

General Purpose Masking Tape - 24 hours, Indoor Use

DESCRIPTION

Scapa Mask 1 is a 0.10mm semi crepe paper tape coated with a rubber based adhesive system, recommended for general purpose indoor masking applications.

APPLICATIONS

- Light weight bundling.
- Professional painters and plasterers masking tape for indoor use.
- Suitable for brush, roller and spray applications. Drying in room temperature condition.
- Suitable for general purpose indoor bonding, holding, sealing and masking applications (24 hours).

PRODUCT BENEFITS

- Interior application only.
- Clean removal at room temperature.
- Smooth and controlled unwind.
- Good peel adhesion.
- Good shear and holding strength.
- Good paint flake resistance.
- No staining.
- Resistant to mild chemicals, lacquers, solvents and water.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2.5	N/cm	AFERA 5001
Elongation at Break	8	%	AFERA 5004
Tensile Strength	35	N/cm	AFERA 5004
Total Thickness	100	µm	AFERA 5006

STANDARD PRESENTATIONS

- Colours: Beige
- Core: 76mm carton Scapa
- Packaging: Individually shrink wrapped with a bar coded label
- Roll Length: 50 metres
- Roll Width: 18, 25, 30, 38, 50, 75 and 100mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Scapa masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature and the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 45° angle with constant speed.