

## Scapa T002

### Medium Firm (MF1) Acrylic Adhesive Transfer Tape - 40 Micron, Neutral

---

#### DESCRIPTION

Scapa T002 is a 40 micron clear acrylic transfer tape coated onto an 80gsm yellow glassine release liner, recommended for splicing, laminating and product assembly applications.

#### APPLICATIONS

- Lamination on to wide variety of materials to make them self-adhesive.
- Flying splice of paper and cardboard.

#### PRODUCT BENEFITS

- Service temperature: -40°C to +150°C
- Good UV resistance and ageing properties.
- Adhesive contains glass fibres for easier converting.
- Acrylic adhesive combining good tack and peel adhesion with high cohesive strength.

*Accreditation:*

*Acid free / pH neutral - compliant to ISO 18902.*

*Photographic activity test (PAT) for enclosure materials - compliant to ISO 18916.*

#### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesive Film Thickness	40	Microns	AFERA 5006
Peel Adhesion on Stainless Steel	6.5	N/25mm	AFERA 5001
Release Liner Thickness	67	Microns	AFERA 5006

## STANDARD PRESENTATIONS

- Branding: neutral core
- Colours: Clear
- Core: 76mm cardboard
- Roll Length: 33 and 50 metres
- Roll Width: 12, 19, 25, 50 and 1,320mm

*Note:*

*19mm x 55 metres also available*

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, we recommend to use the product within 12 months from the date of manufacture.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.