

Scapa Industrial Duct Tapes: Engineered Strength for Every Application



Scapa Industrial offers a comprehensive range of high-performance duct tapes engineered for demanding industrial applications.

Our duct tapes feature pressure-sensitive natural rubber adhesives and polyethylene-coated cloth carriers, providing excellent adhesion, water resistance, and durability across a wide temperature range (-15°C to +75°C).

Designed for versatility, these tapes are ideal for sealing, bundling, masking, and protecting in sectors such as construction, HVAC, and manufacturing.

PRODUCT	MAIN APPLICATION	FEATURES AND BENEFITS	SERVICE TEMPERATURE
3159	General purpose duct tape for industrial applications. Short-term masking, joining PE sheeting for abatement.	<ul style="list-style-type: none"> ✓ Good water resistance, ultimate bond strength. ✓ Good all purpose product. ✓ REACH and RoHS compliant. ✓ Easy tear by hand. 	-15°C/+75°C 5°F/167°F
3160	Sealing, bundling, short-term masking. Medium temperature duct sealing in HVAC. Carpet joining and edging.	<ul style="list-style-type: none"> ✓ Excellent water resistance, ultimate bond strength. ✓ Good all purpose product. ✓ REACH and RoHS compliant. ✓ Easy tear by hand. 	-15°C/+75°C 5°F/167°F
3162	Excellent for asbestos removal (joining of PE sheeting). General purpose duct tape for applications requiring great strength and adhesion.	<ul style="list-style-type: none"> ✓ Excellent water resistance, ultimate bond strength. ✓ Excellent all purpose product. ✓ REACH and RoHS compliant. ✓ Easy tear by hand. 	-15°C/+75°C 5°F/167°F
442R	Color coding, bundling and sealing, taping of metal ductwork, hanging of poly sheeting.	<ul style="list-style-type: none"> ✓ Superior adhesion to poly films. ✓ Easy hand tear, will not twist or curl during application. ✓ High adhesion over a wide temperature range with no "edge-ooze". 	Recommended application temperature 18°C / 65°F
149R	Applications requiring a conformable product and low-residue performance. Taping of metal ductwork.	<ul style="list-style-type: none"> ✓ Easy hand tear, will not twist or curl during application. ✓ No residue upon removal 	Recommended application temperature 18°C / 65°F

Why Choose Scapa Industrial?



Reliable R&D
Support



High quality
products



Manufactured in
an ISO certified
facility



Global
manufacturing
capabilities



Customer
comes first



Shorter
lead times



Contact us today!

www.scapaindustrial.com